KZP...H100 Cable Tray

Overview:

APPLICATION
Cable routing

Material
Hot-dip galv. steel to PN-EN ISO 1461:2011 (HDG)

Available to order:
E- stainless steel (SS)
L- powder coating in a full range of colours (PC)

To join 2 cable tray lengths firmly use either 1 pair of Straight Connector LZCH100 or 1pc of U-Shaped Connector LCC...H100 and 18 sets of Screw SGF M8×14.

Versions:

Sheet thickness: **1,5 mm**

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Weight [1m]	Effective section
KZP100H100/3	**3000**	**100**	**310210**	**4**	**3,95**	**9800**
KZP200H100/3	**3000**	**200**	**310220**	**2**	**5,19**	**19800**
KZP300H100/3	**3000**	**300**	**310230**	**2**	**6,42**	**29800**
KZP400H100/3	**3000**	**400**	**310240**	**2**	**7,66**	**39800**
KZP500H100/3	**3000**	**500**	**310250**	**2**	**8,89**	**49800**
KZP600H100/3	**3000**	**600**	**310260**	**2**	**10,13**	**59800**

Connected products:

KZLP...H100 Cable Tray with Integral Connector

KKZP...H100 90° Horizontal Bend

KKZMP...H100 45° Horizontal Bend

TKZP...H100 Horizontal Tee

CZKZP...H100 Horizontal Cross-over

LZZP...H100 90° Vertical Bend - External

LZZMP...H100 45° Vertical Bend - External

LZWP...H100 90° Vertical Bend - Internal

LZWMP...H100 45° Vertical Bend - Internal

TRZP...H100 Vertical Tee - Lengthwise

RKZP...H100 Straight Reducer

LZCH100 Straight Connector

LCC...H100 U-Shaped Connector

© 2024 STRADER