

KZP...H200 Cable Tray


Overview:

APPLICATION
Cable routing

Material
Hot-dip galv. steel to PN-EN ISO 1461:2011 (HDG)

Available to order:
E- stainless steel (SS)
L- powder coating in a full range of colours (PC)

To join 2 cable tray lengths firmly use either 1 pair of Straight Connector LZCH200 or 1pc of U-Shaped Connector LCC...H200 and 26 sets of Screw SGF M8×14.



Versions:

Sheet thickness: 1,5 mm

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Weight [1m]	Effective section
KZP200H200/3	3000	200	370220	2	7,66	39800
KZP300H200/3	3000	300	370230	2	8,89	59800
KZP400H200/3	3000	400	370240	2	10,13	79800
KZP500H200/3	3000	500	370250	2	11,37	99800
KZP600H200/3	3000	600	370260	2	12,60	119800

Connected products:



KZLP...H200 Cable Tray with Integral Connector
 KKZP...H200 90° Horizontal Bend
 KKZMP...H200 45° Horizontal Bend
 TKZP...H200 Horizontal Tee
 CZKZP...H200 Horizontal Cross-over
 LZZP...H200 90° Vertical Bend - External
 LZZMP...H200 45° Vertical Bend - External
 LZWP...H200 90° Vertical Bend - Internal



LZWMP...H200 45° Vertical Bend - Internal
 TRZP...H200 Vertical Tee - Lengthwise
 RKZP...H200 Straight Reducer
 LZCH200 Straight Connector
 LCC...H200 U-Shaped Connector