


## KZLP...H200 Cable Tray with Integral Connector

### Overview:

**APPLICATION**

Cable routing



**Material**

Hot-dip galv. steel to PN-EN ISO 1461:2011 (HDG)

**Available to order:**

E- stainless steel (SS)

L- powder coating in a full range of colours (PC)


**For the installation use 14 sets of Screw SGF M8x14.**

### Versions:

Sheet thickness: **1,5 mm**

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Weight [1m]	Effective section
KZLP200H200/3	3000	200	372720	2	9,46	39800
KZLP300H200/3	3000	300	372730	2	10,99	59800
KZLP400H200/3	3000	400	372740	2	12,53	79800
KZLP500H200/3	3000	500	372750	2	14,17	99800
KZLP600H200/3	3000	600	372760	2	16,00	119800

### Connected products:



KZP...H200  
Cable Tray

KKZP...H200 90° Horizontal Bend  
KKZMP...H200 45° Horizontal Bend

TKZP...H200  
Horizontal Tee

CZKZP...H200  
Horizontal Cross-over

LZZP...H200 90° Vertical Bend - External

LZZMP...H200 45° Vertical Bend - External

LZWP...H200 90° Vertical Bend - Internal



LZWMP...H200  
45° Vertical Bend - Internal



TRZP...H200  
Vertical Tee - Lengthwise



RKZP...H200  
Straight Reducer