

LZWMC...H200 45° Vertical Bend - Internal

Overview:

APPLICATION

Diversion in cable routing

Material


Hot-dip galv. steel to PN-EN ISO 1461:2011 (HDG)

Available to order:

E- stainless steel (SS)

L- powder coating in a full range of colours (PC)

For joining fittings to cable tray lengths use Straight Connectors LZC...



Versions:

Sheet thickness: **2,0 mm**

Symbol	Width a [mm]	Catalogue number	Quantity in box	Weight 1 pc.
LZWMC200H200	200	372120	2	3,00
LZWMC300H200	300	372130	2	3,47
LZWMC400H200	400	372140	1	3,95
LZWMC500H200	500	372150	1	4,42
LZWMC600H200	600	372160	1	4,88

Connected products:



KZC...H200
Cable Tray



KZLC...H200
Cable Tray with
Integral
Connector



LZCH200
Straight
Connector



LCC...H200
U-Shaped
Connector



LZGCH200
Articulated
Connector



KKZC...H200 90°
Horizontal Bend



KKZMC...H200
45° Horizontal
Bend



TKZC...H200
Horizontal Tee




CZKZC...H200
Horizontal
Cross-over



LZZC...H200 90°
Vertical Bend -
External



LZZMC...H200
45° Vertical
Bend - External



LZWC...H200
90° Vertical
Bend - Internal



TRZC...H200
Vertical Tee -
Lengthwise



RKZC...H200
Straight
Reducer