

## CWZP30H20... Support Channel

### Overview:

**Application**

Used as construction element for installing cable trays and ladders.


**Material**

Hot-dip galv. steel to PN-EN ISO 1461:2011 (HDG)

**Available to order:**

E- stainless steel sections to 3m long (SS)

L- powder coating in a full range of colours (PC)



**Connecting support channel sections through sliding them one into another without the use of any connectors.**

### Versions:

Sheet thickness: **1,5 mm**

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Height H [mm]	Weight [1m]
CWZP30H20/2	2000	30	615120	20	20	0,96
CWZP30H20/3	3000	30	615130	20	20	0,96

### Connected products:

CWZP40H22... Support Channel	CWZP40H47... Support Channel	KTZP35H35... Angle Profile	PLZT30 Perforated Steel Strip	CWZP40H22... Support Channel	CWZP40H47... Support Channel	PLP... Perforated Steel Strip	PTP20... Perforated Steel Band
PZC... Assembly Plate	NO40x20 Protective Cap	CWP40H35... Support Channel	LCW40H35 Channel Connector	LCW40H47 Channel Connector	LCM50H30 Channel Connector	NO40x47 Protective Cap	CP28H12... Channel
CP40H20... Channel	LC40H20 Channel Connector	CMP40H22... Support Channel	KTP25H25... Angle Profile	KTP35H35... Angle Profile	NOK... Protective Cap	NO80x37 Protective Cap	CWP30H30... Support Channel
LCW30H30 Channel Connector	LCM40H40 Channel Connector	TSO... Galvanised Steel Tape	DSO... Galvanised Steel Wire	NO30x30 Protective Cap	NO40x40N Protective Cap	NO40x60 Protective Cap	DPH... I-Beam
NO40x30 Protective Cap	NO50x30 Protective Cap	LCM40H60 Channel Connector	LCM50H50 Channel Connector				