


DUP...H45N Cable Ladder

Overview:

Application
Cable routing

Material
Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

Available to order:
F- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)
E- stainless steel sections to 3m long (SS)
L- powder coating in a full range of colours (PC)



NOTE: Cable ladder with rungs adapted for use with Cable Clamps UK

Available upon special order:

- cable ladders 2m long
- cable ladders 150, 250mm wide
- production capability of perforated rungs

Versions:

Sheet thickness: **1,5 mm**

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Weight [1m]	Effective section
DUP100H45/3N	3000	100	446310	4	2,06	2700
DUP100H45/6N	6000	100	446410	2	2,06	2700
DUP200H45/3N	3000	200	446320	4	2,33	5400
DUP200H45/6N	6000	200	446420	2	2,33	5400
DUP300H45/3N	3000	300	446330	4	2,61	8100
DUP300H45/6N	6000	300	446430	2	2,61	8100
DUP400H45/3N	3000	400	446340	2	3,02	10800
DUP400H45/6N	6000	400	446440	2	3,02	10800
DUP500H45/3N	3000	500	446350	2	3,15	13500
DUP500H45/6N	6000	500	446450	2	3,15	13500
DUP600H45/3N	3000	600	446360	2	3,43	16200
DUP600H45/6N	6000	600	446460	2	3,43	16200

Connected products:



LDC...H45N 90° Horizontal Bend