


## DUP...H45N Cable Ladder

### Overview:

**Application**  
Cable routing

**Material**  
Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

**Available to order:**  
**F-** steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)  
**E-** stainless steel sections to 3m long (SS)  
**L-** powder coating in a full range of colours (PC)



**NOTE: Cable ladder with rungs adapted for use with Cable Clamps UK**

**Available upon special order:**

- cable ladders 2m long
- cable ladders 150, 250mm wide
- production capability of perforated rungs

### Versions:

Sheet thickness: **1,5 mm**

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Weight [1m]	Effective section
DUP100H45/3N	3000	100	446310	4	2,06	2700
DUP100H45/6N	6000	100	446410	2	2,06	2700
DUP200H45/3N	3000	200	446320	4	2,33	5400
DUP200H45/6N	6000	200	446420	2	2,33	5400
DUP300H45/3N	3000	300	446330	4	2,61	8100
DUP300H45/6N	6000	300	446430	2	2,61	8100
DUP400H45/3N	3000	400	446340	2	3,02	10800
DUP400H45/6N	6000	400	446440	2	3,02	10800
DUP500H45/3N	3000	500	446350	2	3,15	13500
DUP500H45/6N	6000	500	446450	2	3,15	13500
DUP600H45/3N	3000	600	446360	2	3,43	16200
DUP600H45/6N	6000	600	446460	2	3,43	16200

### Connected products:



LDC...H45N 90° Horizontal Bend