


DKD...H50N Cable Ladder

Overview:

Application
Cable routing

Material
Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

Available to order:
F- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)
E- stainless steel sections to 3m long (SS)
L- powder coating in a full range of colours (PC)



NOTE: Cable ladder with rungs adapted for use with Cable Clamps UKZ

Available upon special order:
- cable ladders 2m long
- cable ladders 150, 250mm wide.

Versions:

Sheet thickness: 1,2 mm

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Weight [1m]	Effective section
DKD100H50/3N	3000	100	455110	4	1,81	3200
DKD200H50/3N	3000	200	455120	4	2,04	6400
DKD300H50/3N	3000	300	455130	4	2,27	9600
DKD400H50/3N	3000	400	455140	2	2,61	12800
DKD500H50/3N	3000	500	455150	2	2,72	16000
DKD600H50/3N	3000	600	455160	2	2,95	19200

Connected products:

							
LDCH50N Straight Connector	LKDCH50N Angle Connector	LDDCH50N Articulated Connector - Attachable	LGCH50N Articulated Connector	LDP...H50N 90° Horizontal Bend	LDZP...H50N 90° Horizontal Bend - External	TDP...H50N Horizontal Tee	CZDP...H50N Horizontal Cross-over
							
LPDWP...H50N 90° Vertical Bend - Internal	LPDP...H50N Adjustable Vertical Bend	RDSP...H50N Straight Reducer	RDLP...H50N Left Reducer	RDPP...H50N Right Reducer	UKZ1/UKZO1... Cable Clamp	UKZ2... Cable Clamp	