


DKC...H50N Cable Ladder

Overview:

Application
Cable routing

Material
Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

Available to order:
F- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)
E- stainless steel sections to 3m long (SS)
L- powder coating in a full range of colours (PC)



NOTE: Cable ladder with rungs adapted for use with Cable Clamps UKZ

Available upon special order:
 - cable ladders 2m long
 - cable ladders 150, 250mm wide.

Versions:

Sheet thickness: 2,0 mm

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Weight [1m]	Effective section
DKC100H50/3N	3000	100	455710	4	2,90	3200
DKC200H50/3N	3000	200	455720	4	3,26	6400
DKC300H50/3N	3000	300	455730	4	3,64	9600
DKC400H50/3N	3000	400	455740	2	4,18	12800
DKC500H50/3N	3000	500	455750	2	4,36	16000
DKC600H50/3N	3000	600	455760	2	4,73	19200

Connected products:



LDDCH50N Articulated Connector
- Attachable



LDDTH50N Articulated Connector
- Attachable



LDC...H50N 90° Horizontal Bend



UKZ1/UKZ01... Cable Clamp