


## DUD...H50N Cable Ladder

### Overview:

**Application**  
Cable routing

**Material**  
Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

**Available to order:**  
**F-** steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)  
**E-** stainless steel sections to 3m long (SS)  
**L-** powder coating in a full range of colours (PC)



**NOTE: Cable ladder with rungs adapted for use with Cable Clamps UK**

**Available upon special order:**

- cable ladders 2m long
- cable ladders 150, 250mm wide
- production capability of perforated rungs

### Versions:

Sheet thickness: **1,2 mm**

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Weight [1m]	Effective section
<b>DUD100H50/3N</b>	<b>3000</b>	<b>100</b>	<b>456010</b>	<b>4</b>	<b>1,81</b>	<b>3200</b>
<b>DUD200H50/3N</b>	<b>3000</b>	<b>200</b>	<b>456020</b>	<b>4</b>	<b>2,04</b>	<b>6400</b>
<b>DUD300H50/3N</b>	<b>3000</b>	<b>300</b>	<b>456030</b>	<b>4</b>	<b>2,27</b>	<b>9600</b>
<b>DUD400H50/3N</b>	<b>3000</b>	<b>400</b>	<b>456040</b>	<b>2</b>	<b>2,61</b>	<b>12800</b>
<b>DUD500H50/3N</b>	<b>3000</b>	<b>500</b>	<b>456050</b>	<b>2</b>	<b>2,72</b>	<b>16000</b>
<b>DUD600H50/3N</b>	<b>3000</b>	<b>600</b>	<b>456060</b>	<b>2</b>	<b>2,95</b>	<b>19200</b>

### Connected products:



LDDCH50N Articulated Connector - Attachable



LDC...H50N 90° Horizontal Bend