


## DUP...H50N Cable Ladder

### Overview:

**Application**  
Cable routing

**Material**  
Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

**Available to order:**  
**F-** steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)  
**E-** stainless steel sections to 3m long (SS)  
**L-** powder coating in a full range of colours (PC)



**NOTE: Cable ladder with rungs adapted for use with Cable Clamps UK**

**Available upon special order:**

- cable ladders 2m long
- cable ladders 150, 250mm wide
- production capability of perforated rungs

### Versions:

Sheet thickness: **1,5 mm**

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Weight [1m]	Effective section
DUP100H50/3N	3000	100	456310	4	2,18	3200
DUP200H50/3N	3000	200	456320	4	2,45	6400
DUP300H50/3N	3000	300	456330	4	2,73	9600
DUP400H50/3N	3000	400	456340	2	3,14	12800
DUP500H50/3N	3000	500	456350	2	3,27	16000
DUP600H50/3N	3000	600	456360	2	3,55	19200

### Connected products:



LDDCH50N Articulated Connector - Attachable



LDC...H50N 90° Horizontal Bend