


DUC...H50N Cable Ladder

Overview:

Application
Cable routing

Material
Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

Available to order:
F- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)
E- stainless steel sections to 3m long (SS)
L- powder coating in a full range of colours (PC)



NOTE: Cable ladder with rungs adapted for use with Cable Clamps UK

Available upon special order:

- cable ladders 2m long
- cable ladders 150, 250mm wide
- production capability of perforated rungs

Versions:

Sheet thickness: **2,0 mm**

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Weight [1m]	Effective section
DUC100H50/3N	3000	100	456610	4	2,90	3200
DUC200H50/3N	3000	200	456620	4	3,26	6400
DUC300H50/3N	3000	300	456630	4	3,64	9600
DUC400H50/3N	3000	400	456640	2	4,18	12800
DUC500H50/3N	3000	500	456650	2	4,36	16000
DUC600H50/3N	3000	600	456660	2	4,73	19200

Connected products:



LDDCH50N Articulated Connector - Attachable



LDC...H50N 90° Horizontal Bend