


DKC...H60N Cable Ladder

Overview:

Application
Cable routing

Material
Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

Available to order:
F- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)
E- stainless steel sections to 3m long (SS)
L- powder coating in a full range of colours (PC)



NOTE: Cable ladder with rungs adapted for use with Cable Clamps UKZ

Available upon special order:

- cable ladders 2m long
- cable ladders 150, 250mm wide.

Versions:

Sheet thickness: 2,0 mm

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Weight [1m]	Effective section
DKC100H60/3N	3000	100	465710	4	3,22	4200
DKC100H60/6N	6000	100	465810	2	3,22	4200
DKC200H60/3N	3000	200	465720	4	3,57	8400
DKC200H60/6N	6000	200	465820	2	3,57	8400
DKC300H60/3N	3000	300	465730	2	3,96	12600
DKC300H60/6N	6000	300	465830	2	3,96	12600
DKC400H60/3N	3000	400	465740	2	4,50	16800
DKC400H60/6N	6000	400	465840	2	4,50	16800
DKC500H60/3N	3000	500	465750	2	4,68	21000
DKC500H60/6N	6000	500	465850	2	4,68	21000
DKC600H60/3N	3000	600	465760	2	5,05	25200
DKC600H60/6N	6000	600	465860	2	5,05	25200

Connected products:

