

## KCJ...H42 Cable Tray

### Overview:

**Application**  
Cable routing

**Material**  
Steel, strip-galv. acc. to the Sendzimir method to PN-EN 10346:2011 (SG)

**Available to order:**  
F- steel, hot-dip galv. to PN-EN ISO 1461:2011 (HDG)  
E- stainless steel (SS)  
L- powder coating in a full range of colours (PC)

**Important! Possibility of joining cable tray sections together through sliding one into another and connectorfree assembly.**

**Available when ordering in large quantity are 2m and 6m long tray sections. To install cable tray use Screw Sets SGK M6x10 or SG M6x10.**



### Versions:

Sheet thickness: **1,0 mm**

Symbol	Length L [m]	Width a [mm]	Catalogue number	Quantity in box	Weight [1m]	Effective section
KGJ/KCJ50H42/2	2000	50	140505	12	1,08	1900
KGJ/KCJ50H42/3	3000	50	140605	12	1,08	1900
KCJ100H42/3	3000	100	141010	12	1,41	4000
KCJ200H42/3	3000	200	141020	6	2,08	8200
KCJ300H42/3	3000	300	141030	6	2,74	12400
KCJ400H42/3	3000	400	140240	4	3,41	16600
KCJ500H42/3	3000	500	140250	2	4,07	20800
KCJ600H42/3	3000	600	140260	2	4,73	25000

### Connected products:



