

U-strmene, DIN 3570, typ A, V2A - Nerez

Overview:

Field of application

- Simple and efficient attachment of pipes to steel supporting structures, e.g. pipe bridges

Advantages

- Material S235JR (St37) according to DIN 17100 approved for operating temperatures up to 300 °C



Versions:

Symbol	Numer katalogowy	Ilość w opakowaniu	DN	Ø Potrubia [mm]
20 mm	124709	10	15	20
22 mm	124718	10	15	22
25 mm	124724	10	20	25
27 mm	124730	10	20	27
30 mm	124736	10	25	30
34 mm	124742	10	25	34
38 mm	124748	10	32	38
43 mm	124764	10	32	43
45 mm	124770	10	40	45
49 mm	124776	10	40	49
57 mm	124896	10	50	57
61 mm	124902	10	50	61
77 mm	124908	10	65	77
89 mm	124914	10	80	89
108 mm	124988	10	100	108
115 mm	124994	10	100	115
133 mm	125000	1	125	133
140 mm	125006	1	125	140
159 mm	125012	1	150	159
169 mm	125018	1	150	169
191 mm	125024	1	175	191
194 mm	125030	1	175	194
216 mm	125112	1	200	216
220 mm	125118	1	200	220
267 mm	113114	1	250	267
273 mm	113120	1	250	273
318 mm	113126	1	300	318
324 mm	113183	1	300	324
356 mm	113189	1	350	356
368 mm	113195	1	350	368
407 mm	113201	1	400	407
419 mm	113207	1	400	419
508 mm	113213	1	500	508
521 mm	113219	1	500	521