

GDR...- 4-5P/DX/SX Koleno Horizontálne (100-2500A)

Informácie:

Použitie

Slúži na zmenu smeru rovných trás.

- verzie pre 100 až 2500 A
- v 4 a 5 pólovom prevedení
- spájanie dielov svorkovou spojkou
- krytie IP 50, s príslušenstvom možnosť dosiahnuť až IP 55



A	GDR 4		GDR 5	
	DX	SX	DX	SX
100/102/105	GER100102M	GER100101M	GER200102M	GER200101M
400	GER100102	GER100101	GER200102	GER200101
630	GER100106	GER100105	GER200106	GER200105
1250	GER100116	GER100115	GER200116	GER200115
1600	GER116116	GER116115	GER216116	GER216115
2000	GER120116	GER120115	GER220116	GER220115
2500	GER220116	GER220115		

Materiál

- zbernice - meď
- kryt hliník
- štandardé dĺžky 500mm

Verzie:

Symbol	Pól	El. prúd [A]
GDR100102M	4P - DX	100
GDR100101M	4P - SX	100
GDR200102M	5P - DX	100
GDR200101M	5P - SX	100
GDR100102	4P - DX	400
GDR100101	4P - SX	400
GDR200102	5P - DX	400
GDR200101	5P - SX	400
GDR100106	4P - DX	630
GDR100105	4P - SX	630
GDR200106	5P - DX	630
GDR200105	5P - SX	630
GDR100116	4P - DX	1250
GDR100115	4P - SX	1250
GDR200116	5P - DX	1250
GDR200115	5P - SX	1250
GDR116116	4P - DX	1600
GDR116115	4P - SX	1600
GDR216116	5P - DX	1600
GDR216115	5P - SX	1600
GDR120116	4P - DX	2000
GDR120115	4P - SX	2000
GDR220116	5P - DX	2000
GDR220115	5P - SX	2000