


GMT...R1/2 (12kV) Rovný diel 0,6-2m (12kV)

Informácie:

Použitie

Slúži na vytváranie rovných trás.

- verzie pre 12kV
- spájanie dielov skrutkami (v balení)
- krytie IP 40 až IP68



Typ	Výška H [mm]	Dĺžka Lmin [mm]	Dĺžka Lmax [mm]	El. prúd [A]
GMT108R2	182	1001	2000	800
GMT108R1	182	600	1000	800
GMT112R2	182	1001	2000	1250
GMT112R1	182	600	1000	1250
GMT116R2	182	1001	2000	1600
GMT116R1	182	600	1000	1600
GMT120R2	356	1001	2000	2000
GMT120R1	356	600	1000	2000
GMT125R2	356	1001	2000	2500
GMT125R1	356	600	1000	2500
GMT132R2	356	1001	2000	3200
GMT132R1	356	600	1000	3200
GMT140R2	400	1001	2000	4000
GMT140R1	400	600	1000	4000

Typ	Výška H [mm]	Dĺžka Lmin [mm]	Dĺžka Lmax [mm]	El. prúd [A]
GMT108R2	182	1001	2000	800
GMT108R1	182	600	1000	800
GMT112R2	182	1001	2000	1250
GMT112R1	182	600	1000	1250
GMT116R2	182	1001	2000	1600
GMT116R1	182	600	1000	1600
GMT120R2	356	1001	2000	2000
GMT120R1	356	600	1000	2000
GMT125R2	356	1001	2000	2500
GMT125R1	356	600	1000	2500
GMT132R2	356	1001	2000	3200
GMT132R1	356	600	1000	3200
GMT140R2	400	1001	2000	4000
GMT140R1	400	600	1000	4000

Materiál

- zbernice - meď
- kryt - hliník (2mm) , farbený hliník, nerez
- šírka 264 mm

Verzie:

Symbol	Výška H [mm]	Typ	Dĺžka Lmin [mm]	Dĺžka Lmax [mm]	El. prúd [A]
GMT108R2	182	A	1001	2000	800
GMT108R1	182	A	600	1000	800
GMT112R2	182	A	1001	2000	1250
GMT112R1	182	A	600	1000	1250
GMT116R2	182	A	1001	2000	1600
GMT116R1	182	A	600	1000	1600
GMT120R2	356	B	1001	2000	2000
GMT120R1	356	B	600	1000	2000
GMT125R2	356	B	1001	2000	2500
GMT125R1	356	B	600	1000	2500
GMT132R2	356	B	1001	2000	3200
GMT132R1	356	B	600	1000	3200
GMT140R2	400	C	1001	2000	4000
GMT140R1	400	C	600	1000	4000