

GDA...- 4-5P/DX/SX Koleno Vertikálne (250-2500A)

Informácie:

Použitie

Slúži na zmenu smeru rovných trás.

- verzie pre 250 A až 2500 A
- v 4 a 5 pólovom prevedení
- spájanie dielov svorkovou spojkou
- krytie IP 50, s príslušenstvom možnosť dosiahnuť až IP 55



A	4P - 4		4P - 5	
	Symbol	El.	Symbol	El.
250 A	GDA100104	250	GDA100103	250
250 A - 500 A	GDA200104	250	GDA200103	250
500 A	GDA100108	500	GDA100107	500
1000 A	GDA100118	1000	GDA100117	1000
1250 A	GDA116118	1250	GDA116117	1250
2000 A	GDA120118	2000	GDA120117	2000
2500 A	GDA220118	2500	GDA220117	2500

Materiál

- zbernice - hliník
- kryt hliník
- štandardé dĺžky 500mm

Verzie:

Symbol	Pól	El. prúd [A]
GDA100104	4P - DX	250
GDA100103	4P - SX	250
GDA200104	5P - DX	250
GDA200103	5P - SX	250
GDA100108	4P - DX	500
GDA100107	4P - SX	500
GDA200108	5P - DX	500
GDA200107	5P - SX	500
GDA100118	4P - DX	1000
GDA100117	4P - SX	1000
GDA200118	5P - DX	1000
GDA200117	5P - SX	1000
GDA116118	4P - DX	1250
GDA116117	4P - SX	1250
GDA216118	5P - DX	1250
GDA216117	5P - SX	1250
GDA120118	4P - DX	2000
GDA120117	4P - SX	2000
GDA220118	5P - DX	2000
GDA220117	5P - SX	2000