

## GDA...- 4-5P/DX/SX "T" diel (63-2500A)

### Informácie:

#### Použitie

Slúži na rozdelenie a zmenu smeru rovných trás.

- verzie pre 63 A až 2500 A
- v 4 a 5 pólovom prevedení
- spájanie dielov svorkovou spojkou
- krytie IP 50, s príslušenstvom možnosť dosiahnuť až IP 55



N	GDA 4				GDA 5			
	4P	5P	4P	5P	4P	5P	4P	5P
63	100102	100101	200102	200101	100106	100105	200106	200105
250	100106	100105	200106	200105	100116	100115	200116	200115
500	100116	100115	200116	200115	116116	116115	216116	216115
1000	116116	116115	216116	216115	120116	120115	220116	220115
1250	120116	120115	220116	220115	120122	120120	220122	220120
2000	120122	120120	220122	220120				

#### Materiál

- zbernice - hliník
- kryt hliník
- štandardé dĺžky 600/500mm

### Verzie:

Symbol	Pól	El. prúd [A]
GDA100102	4P - DX	63
GDA100101	4P - SX	63
GDA200102	5P - DX	63
GDA200101	5P - SX	63
GDA100106	4P - DX	250
GDA100105	4P - SX	250
GDA200106	5P - DX	250
GDA200105	5P - SX	250
GDA100116	4P - DX	500
GDA100115	4P - SX	500
GDA200116	5P - DX	500
GDA200115	5P - SX	500
GDA116116	4P - DX	1000
GDA116115	4P - SX	1000
GDA216116	5P - DX	1000
GDA216115	5P - SX	1000
GDA120116	4P - DX	1250
GDA120115	4P - SX	1250
GDA220116	5P - DX	1250
GDA220115	5P - SX	1250
GDA120122	4P - DX	2000
GDA120120	4P - SX	2000
GDA220122	5P - DX	2000
GDA220120	5P - SX	2000