

## FLI/... - 2-16P Držiak pre vertikálne uchytenie (800-6300 A)

### Informácie:

#### Použitie

Slúži na upevnenie a zavesenie prípojnicového systému vo vertikálnej polohe.

- verzie pre 800 až 6300 A.



| Model        | 800   | 1250   | 1600   | 2000   | 2500   | 3150   | 4000   | 5000   | 6300   |
|--------------|-------|--------|--------|--------|--------|--------|--------|--------|--------|
| Max. current | 800 A | 1250 A | 1600 A | 2000 A | 2500 A | 3150 A | 4000 A | 5000 A | 6300 A |

| DIMENSIONS<br>(CONDUCTORS) |       |       |
|----------------------------|-------|-------|
| [A]                        | AL    | CU    |
| 800                        | 20 mm | 20 mm |
| 1250                       | 25 mm | 20 mm |
| 1600                       | 25 mm | 25 mm |
| 2000                       | 25 mm | 35 mm |
| 2500                       | 35 mm | 35 mm |
| 3150                       | 35 mm | 45 mm |
| 4000                       | 45 mm | 45 mm |
| 5000                       | 55 mm | 55 mm |
| 6300                       | 75 mm | 55 mm |

### Verzie:

| Symbol | Rozmer a [mm] | Pól |
|--------|---------------|-----|
| FLI/2  | 250           | 2   |
| FLI/3  | 292           | 3   |
| FLI/4  | 334           | 4   |
| FLI/5  | 376           | 5   |
| FLI/6  | 418           | 6   |
| FLI/7  | 460           | 7   |
| FLI/8  | 502           | 8   |
| FLI/9  | 544           | 9   |
| FLI/10 | 586           | 10  |
| FLI/11 | 628           | 11  |
| FLI/12 | 670           | 12  |
| FLI/13 | 712           | 13  |
| FLI/14 | 754           | 14  |
| FLI/15 | 796           | 15  |
| FLI/16 | 811           | 16  |