

GDR...- 4-5P/DX/SX "T" diel (100-2500A)

Overview:

Použitie

Slúži na rozdelenie a zmenu smeru rovných trás.

- verzie pre 100 A až 2500 A
- v 4 a 5 pólovom prevedení
- spájanie dielov svorkovou spojkou
- krytie IP 50, s príslušenstvom možnosť dosiahnuť až IP 55



A	GDR 4		GDR 5	
	DX	SX	DX	SX
100/100/250	GDR100T04	GDR100S04	GDR200T04	GDR200S04
400	GDR100T04	GDR100S04	GDR200T04	GDR200S04
630/630	GDR100T04	GDR100S04	GDR200T04	GDR200S04
1250/1250	GDR100T04	GDR100S04	GDR200T04	GDR200S04
2000/2000	GDR100T04	GDR100S04	GDR200T04	GDR200S04

Materiál

- zbernice - meď
- kryt hliník
- štandardé dĺžky 600/500mm

Versions:

Symbol	Pól	El. prúd [A]
GDR100111M	4P - DX	100
GDR100109M	4P - SX	100
GDR200111M	5P - DX	100
GDR200109M	5P - SX	100
GDR100111	4P - DX	400
GDR100109	4P - SX	400
GDR200111	5P - DX	400
GDR200109	5P - SX	400
GDR100112	4P - DX	630
GDR100110	4P - SX	630
GDR200112	5P - DX	630
GDR200110	5P - SX	630
GDR116122	4P - DX	1250
GDR116120	4P - SX	1250
GDR216122	5P - DX	1250
GDR216120	5P - SX	1250
GDR120122	4P - DX	2000
GDR120120	4P - SX	2000
GDR220122	5P - DX	2000
GDR220120	5P - SX	2000