

## GDA...- 4-5P/DX/SX Koleno Horizontálne (250-2500A)

### Informácie:

#### Použitie

Slúži na zmenu smeru rovných trás.

- verzie pre 250 A až 2500 A
- v 4 a 5 pólovom prevedení
- spájanie dielov svorkovou spojkou
- krytie IP 50, s príslušenstvom možnosť dosiahnuť až IP 55



A	4P - DX				4P - SX			
	1	2	3	4	1	2	3	4
250	GDA100102	GDA100101	GDA100106	GDA100105	GDA100116	GDA100115	GDA100116	GDA100115
500	GDA200102	GDA200101	GDA200106	GDA200105	GDA200116	GDA200115	GDA200116	GDA200115
1250	GDA116116	GDA116115	GDA116116	GDA116115	GDA216116	GDA216115	GDA216116	GDA216115
2000	GDA120116	GDA120115	GDA120116	GDA120115	GDA220116	GDA220115	GDA220116	GDA220115

#### Materiál

- zbernice - hliník
- kryt hliník
- štandardé dĺžky 500mm

### Verzie:

Symbol	Pól	El. prúd [A]
GDA100102	4P - DX	250
GDA100101	4P - SX	250
GDA200102	5P - DX	250
GDA200101	5P - SX	250
GDA100106	4P - DX	500
GDA100105	4P - SX	500
GDA200106	5P - DX	500
GDA200105	5P - SX	500
GDA100116	4P - DX	1000
GDA100115	4P - SX	1000
GDA200116	5P - DX	1000
GDA200115	5P - SX	1000
GDA116116	4P - DX	1250
GDA116115	4P - SX	1250
GDA216116	5P - DX	1250
GDA216115	5P - SX	1250
GDA120116	4P - DX	2000
GDA120115	4P - SX	2000
GDA220116	5P - DX	2000
GDA220115	5P - SX	2000