


GMT...AV/AVM (12kV) Koleno Vertikálne (12kV)

Informácie:

Použitie

Slúži na zmenu smeru rovných trás.

- verzie pre 12kV
- spájanie dielov skrutkami (v balení)
- krytie IP 40 až IP68



#	12kV		12kV	
	12kV	12kV	12kV	12kV
1	800	1250	1600	2000
2	800	1250	1600	2000
3	800	1250	1600	2000
4	800	1250	1600	2000
5	800	1250	1600	2000
6	800	1250	1600	2000
7	800	1250	1600	2000
8	800	1250	1600	2000
9	800	1250	1600	2000
10	800	1250	1600	2000
11	800	1250	1600	2000
12	800	1250	1600	2000
13	800	1250	1600	2000
14	800	1250	1600	2000
15	800	1250	1600	2000
16	800	1250	1600	2000
17	800	1250	1600	2000
18	800	1250	1600	2000
19	800	1250	1600	2000
20	800	1250	1600	2000
21	800	1250	1600	2000
22	800	1250	1600	2000
23	800	1250	1600	2000
24	800	1250	1600	2000
25	800	1250	1600	2000
26	800	1250	1600	2000
27	800	1250	1600	2000
28	800	1250	1600	2000
29	800	1250	1600	2000
30	800	1250	1600	2000
31	800	1250	1600	2000
32	800	1250	1600	2000
33	800	1250	1600	2000
34	800	1250	1600	2000
35	800	1250	1600	2000
36	800	1250	1600	2000
37	800	1250	1600	2000
38	800	1250	1600	2000
39	800	1250	1600	2000
40	800	1250	1600	2000
41	800	1250	1600	2000
42	800	1250	1600	2000
43	800	1250	1600	2000
44	800	1250	1600	2000
45	800	1250	1600	2000
46	800	1250	1600	2000
47	800	1250	1600	2000
48	800	1250	1600	2000
49	800	1250	1600	2000
50	800	1250	1600	2000
51	800	1250	1600	2000
52	800	1250	1600	2000
53	800	1250	1600	2000
54	800	1250	1600	2000
55	800	1250	1600	2000
56	800	1250	1600	2000
57	800	1250	1600	2000
58	800	1250	1600	2000
59	800	1250	1600	2000
60	800	1250	1600	2000
61	800	1250	1600	2000
62	800	1250	1600	2000
63	800	1250	1600	2000
64	800	1250	1600	2000
65	800	1250	1600	2000
66	800	1250	1600	2000
67	800	1250	1600	2000
68	800	1250	1600	2000
69	800	1250	1600	2000
70	800	1250	1600	2000
71	800	1250	1600	2000
72	800	1250	1600	2000
73	800	1250	1600	2000
74	800	1250	1600	2000
75	800	1250	1600	2000
76	800	1250	1600	2000
77	800	1250	1600	2000
78	800	1250	1600	2000
79	800	1250	1600	2000
80	800	1250	1600	2000
81	800	1250	1600	2000
82	800	1250	1600	2000
83	800	1250	1600	2000
84	800	1250	1600	2000
85	800	1250	1600	2000
86	800	1250	1600	2000
87	800	1250	1600	2000
88	800	1250	1600	2000
89	800	1250	1600	2000
90	800	1250	1600	2000
91	800	1250	1600	2000
92	800	1250	1600	2000
93	800	1250	1600	2000
94	800	1250	1600	2000
95	800	1250	1600	2000
96	800	1250	1600	2000
97	800	1250	1600	2000
98	800	1250	1600	2000
99	800	1250	1600	2000
100	800	1250	1600	2000

Materiál

- zbernice - meď
- kryt - hliník (2mm) , farbený hliník, nerez
- šírka 264 mm

Verzie:

Symbol	Výška H [mm]	Typ	El. prúd [A]	Dĺžka LxL [mm]
GMT108AV	182	A	800	600x600
GMT108AVM	182	A	800	na požiadanie
GMT112AV	182	A	1250	600x600
GMT112AVM	182	A	1250	na požiadanie
GMT116AV	182	A	1600	600x600
GMT116AVM	182	A	1600	na požiadanie
GMT120AV	356	B	2000	600x600
GMT120AVM	356	B	2000	na požiadanie
GMT125AV	356	B	2500	600x600
GMT125AVM	356	B	2500	na požiadanie
GMT132AV	356	B	3200	600x600
GMT132AVM	356	B	3200	na požiadanie
GMT140AV	400	C	4000	600x600
GMT140AVM	400	C	4000	na požiadanie